

Rolltite Quote Form



Richards-Wilcox
Garage Doors

Date
Dealer name
First/Last name
Project name
Door tag #

R300 Econo rolling	R600 Insulated
R400 Rolling	R700 Shutter
R500 Fire and shutter door	

Quantity (identical doors)	Width	ft	in
	Height	ft	in
Quantity (other door)	Width	ft	in
	Height	ft	in

Mounting				
Interior		Exterior		
Location				
Face of wall		In-between	Face/between	
Jamb type				
Metal		Wood	Concrete	Hollow block
Slats				
Flat		Curved		
Slats gauge				
24	22	20	18	16
Slats finish				
Painted:		White	Grey	Tan
Galvanised				
RAL:		#	Complete	Partial
Insulating				
FIP (foam)		LIP (polystyrene)	FIP default with R600	
Material				
Guide:		Steel	Stainless	Aluminum
Hood:		Steel	Stainless	Aluminum
BBAR:		Steel	Stainless	Aluminum
R7225 shutter model is all stainless				
Guides				
Leg in E		Leg out Z		
Endlock				
Standard		Windlock		
Hood				
24ga		22ga		
Fascia		Y	N	
Locks				
Slide		Cylinder	Best cylinder	
Weatherseal				
Jambs (vertical)		Brush	Vinyl (clip on)	
Header				
Hood baffle				
Bottom bar				
Standard with astragal		Stainless		

Operation			
Spring cyles:	25K	50K/100K	
Drive side:	Right	Left	
Manual	Chain hoist	Crank	
Motorized	Stainless	Motor by other	
Mount:	Front of hood	with bracket	w/o bracket
	Wall mount	with bracket	w/o bracket

Motorized		
HP	Voltage	Phase
Standard Gearhead		

Accessories		
Sensing edge:	Pneumatic	Electric
Interlock	Y	N
Remote	Y	N
Comments:		

Options		
Vision slats (must be a flat slat)	Y	N
Perforated	Y	N
Slopped bottom bar	Y	N
Hot dipped:	Bottom bar	Guide

Fire doors			
XP	XPBB	AFCB	XPBB default for a release system
Horn	Strobe	Smoke detector	
U.L. rating:	45 min	90 min	
	3 h	4 h	
Smoke package NFPA 105			

Paint/ Custom RAL		
Curtain (see slat finish)	Hood (see slat finish)	Fascia (standard: same as hood)
Guides (standard: black)	Bottom bar (standard: black)	

Comments

Rolltite **R800** Grille Quote Form



Richards-Wilcox
Garage Doors

Date _____

Dealer name _____

First/Last name _____

Project name _____

Door tag # _____

Quantity (identical doors)	Width	ft	in
	Height	ft	in
Quantity (other door)	Width	ft	in
	Height	ft	in

Mounting

Interior Exterior

Location

Face of wall In-between Face/between

Jamb type

Metal Wood
Concrete Hollow block

Grille

Straight grill Perforated Solid aluminium
Brick pattern Polycarbonate

Material (aluminum)

Guide

Hood

BBAR

Guides

Leg in E Leg out Z

Endlock

Standard Windlock

Hood

24ga 22ga

Fascia Y N

Locks

Slide Cylinder Best cylinder

Operation

Spring cyles: 25K 50K/100K

Drive side: Right Left

Manual Chain hoist Crank

Motorized Stainless Motor by other

Mount: Front of hood with bracket w/o bracket

Wall mount with bracket w/o bracket

Motorized

HP Voltage Phase

Standard Gearhead

Accessories

Sensing edge: Pneumatic Electric

Interlock Y N

Remote Y N

Notes:

Comments

Please email form to rolltite@rwdoors.com